



BLTEK

POWERED BY:
XPCS
GROUP

NEON LED FLEX



NEON LED FLEX

Item No.	CCT	Length (mm)	LED QTY	LED	Power (W/m)	Input voltage (v)	Work in current (A/m)	lm/m	Beam angle (*)	IP	CRI	PF	Working temperature
CL-2835XW120SY24-T1010	3000	1000	120	2835	9.6	DC24V	0.40	480	180	IP67	80	/	- 20 ~ + 45°C
	4000	1000	120	2835	9.6	DC24V	0.40	480	180	IP67	80	/	- 20 ~ + 45°C
	6000	1000	120	2835	9.6	DC24V	0.40	480	180	IP67	80	/	- 20 ~ + 45°C



3000K / 4000K / 6200K



480 lm/m



DC12V



9,6W/m



IP65







>80



120 Led/m




12x0.35mm




Não fazer pressão excessiva na superfície da fita de luz (vidro/painéis) de acrílico etc




Não cobrir a tira de Leds com nenhum material




Não ligar a tira de Leds quando enrolada na bobine.



Não forçar a tira de Leds em diâmetros inferiores a 38 milímetros



Não dobrar, vincar ou torcer, a tira de Leds.



Não forçar horizontalmente a tira de Leds.



BLTEK

POWERED BY:
XPCS
GROUP

Rua General Humberto Delgado, 161, 1dto | 4445-123 - Alfena - Portugal
Mail: xpcs.lda@gmail.com | www.xpcs.pt